

iradio

PORTABLE TWO-WAY RADIO



Function

- Output power:VHF5W/UHF5W
- Switch between high output and low output
- Scan function with all channels scan and priority
- Built-in 50 CTCSS and 104 DCS



I-620



iradio

PORTABLE TWO-WAY RADIO

- VHF 5W/UHF5W
- With emergency alarm
- With VOX
- Scan function with all channels scan and priority
- FM
- Monitor
- Built-in 50 CTCSS and 104 DCS,end-tone elimination
- Chinese/English software programming
- PC programming
- Cloning

GENERAL		TRANSMITTER		RECEIVER	
Frequency Range	VHF 136-174MHz UHF 400-470MHz	RF Output Power	≤5W	(12dB SINAD)Sensitivity(12dB SINAD)	0.18uV
Channel Capacity	16	Modulation Type	F3E	Selectivity	55dB
Operation Voltage	7.2VDC±15%	Modulation Distortion	<5%	Adjacent Channel Selectivity	≤70d
Antenna Impedance	50Ω	Maximum Deviation	<5KHz	Audio Power Output	500mW When Distortion
Channel Spacing	25KHz	Adjacent Channel Power	≥65dB	Audio Distortion	<5%
Working Temperature	-30℃~ 60℃	Spurious Radiation	≤7.5uW		
Frequency Stability	±2.5PPM				
Dimension (without antenna)	105X58X35mm				

COURS ESOFFERED



Battery



Charger



AC Adapter



Belt Clip



Antenna

Quanzhou Iradio Science & Technology Co., Ltd Distributor

