

SUUNTO KB14/360RG COMPASS



- Accuracy 1/3°
- Graduation interval 0.5°
- Scale: Azimuth 360°, Reversed 360°
- Adjustable diopter
- Sapphire bearing
- Liquid filled capsule for stable operation
- Anodized light-alloy housing
- Nylon pouch with belt-loop
- Lanyard
- Made in Finland

Specifications

TECHNICAL SPECIFICATIONS

GENERAL

| | |
|------------------|---------------------|
| Lens material: | Acrylic |
| Weight | 93 g |
| Battery type | no battery required |
| Tripod mount | √ |
| Conversion table | cotangent 0-45° |
| Carrying pouch | √ |
| Attachment | lanyard |

COMPASS

| | |
|---------------------------------|---------|
| Direction scale | degrees |
| Needle | card |
| Globally balanced | √ |
| Liquid filled and jewel bearing | √ |
| Adjustable optics | √ |
| Compass accuracy | 1/3° |
| Compass resolution | 1/2° |

PHYSICAL SPECIFICATIONS

| | |
|-----------------------|--------------------------------------|
| Operating temperature | -30° C to +60° C / -22° F to +140° F |
| Storage temperature | -30° C to +60° C / -22° F to +140° F |

OUTDOOR FUNCTIONS

GPS TRACKING & NAVIGATION

| | |
|----------|--------|
| Sighting | optics |
|----------|--------|