## **GINTEC**

## GINTEC \$50 BROCHURE

The Gintec S50 is an intelligent Android-based terminal ideal for highly mobile field work in applications such as survey, military, construction, mining, logistics, and other outdoor-heavy sectors. It meets MIL-STD-810G and IP67 standards for durability and protection against dust water, impact, vibration, temperature and other factors that would quickly damage an industrial-grade table. The S50 also comes with a ultra-long-life 5000 mAh battery, sunlight-readable screen, and a suite of integrated sensors such as a camera, on-board GPS, and IMU.





## **TECHNICAL SPECIFICATIONS**

Processors	1.5GHzx4 Cortex A53 Quad Core 64bit GSM 850/900/1800/1900 WCDMA 850/2100,1GB+16GB,8.0MP with OTG,GPS,WI-FI,BT	Accessories	USB cable x 1, charger x 1, user manual x 1 and gift box x 1
		Touch Panel	G+G5 5 Points capacitance screen
Main Display	4.5"QHD IPS/AFFSLCD 960*540 Sunlight Readable Touch Panel G+G5 5 Points capacitance screen	Dimensions	197 x 92 x 26.5 mm (LxWxH)
		Weight	380 g

**HARDWARE** 

Chipset Cortex A53 Quad Core 1.5G

Hzx4

Frequency (MHZ) WCDMA 850/2100 (850/1900

option) &

GSM850/900/1800/1900

Sim Card Yes

Android 5.1

Satellite Navigation GPS chip

built-in, support A-GPS, EPO

OTG/FM Radio/

Motion sensor/ **Gravity Sensor** 

Support

Magnetic Field

Senso/Gyroscope

Sensor

Support

Bluetooth

Support NFC Optional Speaker Single 2030

**CAMERA** 

Main Camera 8.00MP(AF) with flash led Barcode Scanner 1D/2D Barcode Scanner

**MEMORY** 

Internal Memory **External Memory** 

3GB RAM + 32GB ROM Micro SD card (T-FLASH

card), max 64GB

5000mAh

**BATTERIES & 10** 

Capacity (mAh)

Earphone 3.5 mm

USB Micro 5Pin Charger USB Micro 5Pin Connector

**NETWORK** 

WCDMA 3.75G(HS

PA+42.2Mbps, HSUPA+11.5Mbps)

TD-SCMA

4G fdd: UP TO 150Mbds, 50Mbps

uplink, tdd: up to 150 Mbps

downlink, 50 Mbps uplink

**EDGE** Support WAP Support Support WIFI Support **OTHERS** 

Data Collection UHF RFID (1-3m)

**GNSS** Barcode scanner

HF RFID/NFC

Certification

Serial Port RS232/TTL 3.3Vx3/GPIO

3.3Vx3/200ma VBTX2

Internal Space 32mm x 32mm x 5mm x 1

Shakeproof:1-19Hz/1.0mm; **Environmental Test** 

19-200Hz/1.0g

Drop-proof: MIL-STD-810G

Method

516.6/Procedure IV Water-proof: Class 7 Dust-proof: Class 6

Soundness:MTBF>50000h;

MTTR<0.5h

## YOUR LOCAL DEALER:



**INTEC MARKETING SERVICES SDN BHD** LOT 8678, PENDING COMMERCIAL CENTRE JALAN PENDING, KUCHING, 93450 SARAWAK, MALAYSIA

Phone: +6082 344 596 sales@intec.com.my Website: www.intec.com.my