

# SOKKIA

MADE TO FIT YOUR WORLD.

## SA300

Dual-Constellation, Dual-Frequency Antenna



# SA300

## Dual-Constellation, Dual Frequency Antenna

- Precision-tuned
- Micro-centered design
- Rugged enclosure with high-shock and vibration tolerance

### Dual-Frequency Dual-Constellation Antenna

The SA300 high-precision micro-centered antenna with integrated ground plane provides excellent tracking sensitivity and multipath rejection for all surveying applications. The SA300 antenna supports L1/L2 frequencies from GPS and GLONASS satellite constellations. The SA300 can be paired with applicable Sokkia GNSS receivers to provide a high-performance dual-frequency RTK system.

The SA300 antenna system offers IP67 dust and water resistance as well as superior level of vibration and shock tolerance (IEC 60068-2). With its compact and ultra-rugged design, the SA300 is the most robust antenna in the market today.

### Related Products

#### Sokkia GHX2 Network Rover System

The GHX2 network rover system is an all-in-one handheld GNSS receiver and field controller featuring a high-speed processor, increased memory, cellular modem, Bluetooth®, and Wi-Fi.

SPECIFICATIONS	
<b>Operating Frequency Range</b>	
Telescope	1586.5 ± 25MHz
Magnification / Resolving power	1236 ± 20MHz
<b>Out of Band Rejection</b>	
L1	± 100MHz -30 dBc (typical)
L2	± 200MHz -60 dBc (typical)
<b>Gain, Noise Figure and VSWR</b>	
LNA Gain	33 dB (typical)
Gain at Zenith (90°)	GPS L1 5.5 dBc (min) GPS L2 5.5 dBc (min) GLONASS L1 4.5 dBc (min) GLONASS L2 4.5 dBc (min)
Noise Figure	1.5 dB (typical)
VSWR	≤ 2.0:1
Nominal Impedance	50 Ohms
<b>Connector and Mounting</b>	
Antenna Connector	TNC
Mount	5/8-11 UNC-2B thread
<b>Physical Characteristics</b>	
Dimension (W x H x L)	141.6 x 141.6 x 54.2 mm
Weight	615g
Centering	< 1mm, micro-centered
<b>Power</b>	
Input Voltage Range	3-18 VDC. Reverse Polarity Protected
Power Consumption	55mA (typical)
<b>Environmental</b>	
Enclosure	Aluminum with Plastic Radome
Operating temperature	-50°C to 85°C
Storage Temperature	-55°C to 85°C
Dust and Water Protection	IP67
Random Vibration	IEC 60068-2-34, Test Fd
Sinusoidal Vibration	IEC 60068-2-6, Test Fc
Shock	IEC 60068-2-29 Test Ea
Bump	IEC 60068-2-29 Test Eb
Drop	2 m pole drop to concrete

# SOKKIA

sokkia.com

Specifications subject to change without notice  
©2018 Topcon Corporation All rights reserved.  
SOK-1026 Rev B 8/18

Your local Authorized Dealer is: